

# APPLICATION DATA SHEET



**ENVIROGRAF®**

AP042-HW ACRYLIC-07-2015

## Product Number: 42 HW Acrylic White Top Coat

### **Description:**

This acrylic emulsion coating is for use over HW01, ES/VFR White and EP/CP. Ideal for plasterboard, lath-and-plaster and as a coating for plaster, masonry, etc.

### **Coverage:**

Two coats applied at 12m<sup>2</sup> per litre per coat.

### **Preparation and Application:**

All surfaces should be clean, dry and free from contamination.

HW Acrylic can be applied by brush, roller or spray. Can be thinned with up to 5% clean water. Stir well before application. The result is dependent on the condition of the substrate and temperature of application.

### **Tools and Storage:**

Clean tools and spillages immediately with warm water.

Containers must be kept tightly closed and stored at a minimum temperature of 5°C and a maximum temperature of 35°C.

### **Precautions:**

- Ensure good ventilation during application and drying. Do not inhale vapour or spray mist
- Wash hands after use and before handling food.
- Avoid contact with skin and eyes. Wear suitable protective clothing including gloves and eye/face protection. Wear a mask when spraying.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner. Do not use solvent or thinners.
- Do not ingest. If swallowed seek medical advice immediately.
- Keep out of the reach of children.