

APPLICATION DATA SHEET



ENVIROGRAF®

AP042-HW04/S-UC-11-2014

Product Number: 42

HW04/S Undercoat White Spirit Based

Description:

HW04/S White is a flexible protective coating for use over HW01/F intumescent coating

Coverage:

Approximately 17m² per litre depending on the number of coats applied.

Preparation and Application:

All surfaces should be clean, dry and free from contamination, with no loose particles.

Stir well before application. May be applied using brush or roller. The result is dependent on the condition of the substrate and temperature of application. Do not thin and do not use over polystyrene. Touch dry in 4 – 6 hours. Re-coatable in 16 to 24 hours at 20°C.

Tools and Storage:

Clean tools and spillages immediately with white spirit.

Keep containers in a dry, cool, well ventilated space away from heat. Containers must be kept tightly closed and stored at a minimum temperature of 5°C and a maximum temperature of 35°C.

Precautions:

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner. Do not use solvent or thinners.
- If swallowed seek medical advice immediately.
- Keep out of the reach of children.