

APPLICATION DATA SHEET



ENVIROGRAF®

AP083-INTERSHIELD TOP COAT-01-2020

Product Number: 83

Intershield Flexible Top Coat

Description:

This is a chlorinated rubber flame retardant coating, complying with BS476 Parts 6 & 7, Class 0 & Class 1 (1987) Spread of flame.

Coverage:

Approximately 8 - 10m² per litre per coat. Two coats required.

Preparation and Application:

All surfaces should be clean, dry and free from contamination.

Intershield Flexible Top Coat is ready for use and does not need thinning. Stir well before application. The result is dependent on the condition of the substrate and temperature of application.

Drying times:

Touch dry – 30 to 60 minutes

Recoat - a minimum of 4 to 6 hours when sprayed, 14 to 16 hours if applied by brush or roller

Hard dry – 24 hours

Tools and Storage:

Clean tools and spillages immediately with white spirit

Keep containers in a dry, cool, well ventilated space away from heat. Containers must be kept tightly closed and stored at a minimum temperature of 5°C and a maximum temperature of 35°C.

Precautions:

- Ensure good ventilation during application and drying. Do not inhale vapour or spray mist
- Avoid contact with skin and eyes. Wear suitable protective clothing including gloves and eye/face protection
- In case of contact with eyes, rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so and continue rinsing.
- In case of contact with skin, remove contaminated clothing immediately. Rinse skin with water and wash thoroughly with soap and water or recognized skin cleaner. Do not use solvents or thinners.
- If swallowed seek medical advice immediately. Do not induce vomiting
- Keep out of the reach of children.
- Dispose of this material and container only to a waste collection point dealing in hazardous or special waste. Avoid release to the environment.