

# APPLICATION DATA SHEET



**ENVIROGRAF®**

AP092-QVFR-UVR CLEAR-08-2018

## Product Number: 92 QVFR-UVR Clear Top Coat

### **Description:**

A solvent based product to apply over QVFR Clear – no need for an undercoat. Available in Matt, Satin or Gloss finishes. It contains a UV filter for protection against blistering, cracking and peeling. For internal use.

### **Application:**

All surfaces to be painted should be clean, dry and free from loose and flaking material. Stir QVFR-UVR well before and during use. Apply using brush or roller. QVFR-UVR is supplied ready for use and does not need thinning.

For internal use apply 1 coat at 10 – 12m<sup>2</sup> per litre  
(Ensure end grain is treated with each coat)

### **Cleaning and storage:**

Remove as much product as possible from brushes before cleaning. Clean equipment immediately after use with white spirit or turpentine substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

To avoid risk of spillage, always store and transport in a secure upright position.

STORE AWAY FROM HEAT AND FLAME

### **Precautions:**

- Keep away from sources of ignition – No Smoking
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner. Do not use solvent or thinners.
- If swallowed seek medical advice immediately and show container or label.
- Keep out of the reach of children.