

APPLICATION DATA SHEET



ENVIROGRAF®

AP118-11-2019

Product Number: 118

Animal Door Flap Protection

Description:

Your standard animal door flap (not supplied) fits into our metal frame unit. Standard finishes are brown, white or grey. The inside of the metal unit has a drop curtain held by a thermal cut-out which once the temperature or the cat flap reaches 70°C the curtain drops giving 60 minutes fire protection. Please Note: Product 118 Animal Door Flap Protection is not suitable for use with aluminium animal door flap units.

Application:

A rectangular or square opening is cut into the door or wall as specified for the particular unit (Petsafe/Staywell etc.) For example, for an opening of 348mm x 225mm specified by the flap manufacturer, the opening for the Envirograf® fire protection unit would need to be cut to 418mm x 295mm. Each unit supplied has its own hole cutting requirements and these should be checked when ordering. (See technical data sheet or price list for full range of sizes)

The Envirograf® fire protection unit is supplied in two sections. The first part fits into the outside of the door or wall and is fixed using screws (not supplied). The second part fits through the inside of the opening, into the first part and is also fixed using screws (not supplied). The original branded cat/dog flap then screws to the face of the Envirograf® fire protection unit so it will be necessary to drill small holes in the metal face of the unit for the screws from the cat/dog flap.

