



Product Number: 151

Fire Protection Coating for UPVC

UP30WB, Firocoat SB, Firocoat WB

Description:

This coating system is designed to upgrade new and existing UPVC window frames and doors, offering up to 30 minutes fire protection meeting both UK National and European Fire Regulations.

Application:

UP30WB

Ensure the surface is dry, clean and free from dust. Stir UP30WB well before applying. If UP30WB thickens slightly, stand the paint can in hot water and stir well. Up to 5% warm water may be added if required. For spraying, add up to 10% warm water but ensure the correct amount of material is applied. Apply two coats of UP30WB at 6m² per litre per coat. Can be applied using brush, roller or spray. Ensure each coat is completely dry before applying subsequent coats. Firocoat SB top coat or Firocoat WB top coat must be applied once the UP30WB has dried.

Firocoat SB

White satin finish spirit based top coat. For external use apply two coats of Firocoat spirit based top coat at 10 – 12m² per litre per coat.

Firocoat WB

White satin finish water based top coat. For internal use apply two coats of Firocoat water based top coat at 10 – 12m² per litre per coat.

Tools and storage:

Water-Based Products – wash with warm water. White Spirit Based Products – clean with white spirit or a brush cleaner. Envirograf® recommends that the products are stored in temperatures between 5°C and 30°C. When transporting or storing the tins ensure that the product is not exposed to freezing conditions. Do not apply the product in temperatures less than 5°C.

Always check that the Product is within its shelf life. If in doubt contact your supplier.