



Product Number: 42 HW Excel White Top Coat

Description:

A solvent based product to apply over HW01 – no need for an undercoat. Available in Satin or Gloss finishes. Gives a high quality durable finish for internal & external use. Suitable for use on all types of timber substrate.

Coverage:

HW Excel white is supplied ready for use and does not need thinning.
For internal use apply 1 coat at 10 – 12m² per litre
For external use apply 2 coats at 10 – 12m² per litre per coat
(Ensure end grain is treated with each coat)

VOC Content:

High VOC content: 25 – 50%
EU limit value for this product (Cat A/d): 500g/l (2007) / 400g/l (2010)
This product contains max 400g/l VOC

Ordering references:

HW Excel + size required (available in 1 litre, 2.5 litre and 5 litre containers)

Can be supplied to RAL colours on request (extra charge applies). Please call technical department for further details.

SAFETY DATA SHEET



ENVIROGRAF®

HS042-EXCEL WHITE -11-2018

Product Number: 42 HW Excel White Top Coat

Description:

A solvent based product to apply over HW01 – no need for an undercoat. Available in Satin or Gloss finishes. Gives a high quality durable finish for internal & external use. Suitable for use on all types of timber substrate.

This product comprises of the following materials and therefore is supported by Health & Safety Data Sheets:

- (Appendix 71a) HW Excel White Satin
- (Appendix 71b) HW Excel White Gloss

*The information contained in this safety data sheet is given in good faith. It is accurate to the best of our knowledge and belief and represents the most up to date information. The information given in this data sheet does not constitute or replace the user's own assessment of workplace risk as required by other health and safety legislation.

HEALTH & SAFETY INFORMATION SHEET

APPENDIX 71a

HW EXCEL WHITE - SATIN

1. IDENTIFICATION OF THE PREPARATION AND COMPANY

1.1 Product identifier

Product name : HW Excel white – satin
Product code : Not available
Other means of identification : Not available

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Consumer applications, Professional applications
Use of the substance/mixture : Coating

1.3 Details of the supplier of the safety data sheet

Envirograf

Envirograf House, Barfrestone, Dover, Kent, CT15 7JG

Telephone/fax/email: 01304 842555 01304 842666 sales@envirograf.com

1.4 Emergency telephone number: **Supplier:** 01304 842555 (Not 24 Hours)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification According to Regulation (EC) No. 1272/2008 [CLP/GHS]: Flam. Liq. 3, H226

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label Elements

Hazard pictograms :



Signal word : Warning

Hazard statements : Flammable liquid and vapour

Precautionary statements

General : Keep out of reach of children. If medical advice is needed, have product container or label at hand

Prevention : Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames & other ignition sources . No Smoking

Response : IF ON SKIN (or hair): Immediately take off all contaminated clothing. Rinse skin with water or shower

Storage : Store in a well-ventilated place. Keep cool

Disposal : Dispose of contents & container in accordance with all local, regional, national & international regulations
P102, P101, P280, P210, P303 + P361 + P353, P403, P235, P501

Hazardous ingredients : Not applicable

Supplemental label elements: Contains 2-butanone oxime. May produce an allergic reaction.

Annex XVII- Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles: Not applicable

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable

Tactile warning of danger : Not applicable

2.3 Other hazards

Other hazards which do not result in classification: Prolonged or repeated contact may dry skin & cause irritation

3. COMPOSITION / INFORMATION ON INGREDIENTS

3.2 Mixtures :Mixture

Product/ingredient name	Identifiers	%	Classification Regulation (EC) No. 1272/2008 [CLP]	Type
Hydrocarbons, C9-C11 n-alkanes, isoalkanes cyclics, <2% aromatics	REACH # 01-2119463258-33 EC: 919-857-5 CAS: 64742-48-9	≥ 10- <20	Flam.Liq 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066	[1]
Naphtha (petroleum) hydrotreated heavy: Nota(s) P	EC: 265-150-3 CAS:64742-48-9 Index: 649-327-00-6	≥ 5 – ≤10	Flam. Liq. 3, H226 Asp. Tox. 1, H304 EUH066	[1]
Distillates (petroleum) hydrotreated light	EC: 265-149-8 CAS: 64742-47-8 Index: 649-422-00-2	≥1.0 - ≤5.0	Asp. Tox. 1, H304	[1]
Hydrocarbons, C10-C13, n-alkanes, Isoalkanes, cyclics <2% aromatics	REACH # 01-2119457273-39 EC: 918-481-9 CAS: 64742-48-9	≥1.0 - ≤5.0	Asp. Tox. 1, H304 EUH066	[1]
Hydrocarbons, C14-C18, n-alkanes, Isoalkanes, cyclics <2% aromatics	REACH #: 01-2119457736-27 EC: 927-632-8 CAS: 64742-47-8	≥1.0 - ≤5.0	Asp. Tox. 1, H304* EUH066	[1]
2-butanone oxime	REACH #: 01-2119539477-28 EC: 202-496-6 CAS: 96-29-7 Index: 616-014-00-0	<1.0	Acute Tox. 4, H312 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351	[1]
2-ethylhexanoic acid, Zirconium salt	REACH #: 01-2119979088-21 EC: 245-018-1 CAS: 22464-99-9	≤3.0	Repr.2, H361fd (Fertility & Unborn Child) (oral) See Section 16 for the full text of H Statements declared above	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8

SUB codes represent substances without registered CAS Numbers.

4. FIRST AID MEASURES

4.1 Description of first aid

Eye contact: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelid seek immediate medical advice.

Inhalation: Remove to fresh air, keep patient warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin Contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or a recognized skin cleaner. DO NOT USE SOLVENT OR THINNERS.

Ingestion: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. DO NOT induce vomiting

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact : No known significant effects or critical hazards

Inhalation : No known significant effects or critical hazards
Skin contact : Defatting to the skin. May cause skin dryness and irritation
Ingestion : No known significant effects or critical hazards

Over-exposure signs/symptoms

Eye contact : No specific data
Inhalation : No specific data
Skin contact : Adverse symptoms may include: irritation, dryness, cracking
Ingestion : No specific data

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled

Specific treatments: No specific treatment.

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Use dry chemical, CO₂, water spray (fog) or foam

Unsuitable extinguishing media: Do not use water jet

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture: Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard

Hazardous combustion products: Decomposition products may include the following materials: carbon dioxide, carbon monoxide, metal oxide/oxides

5.3 Advice for firefighters

Special precautions for Firefighters: Promptly isolate the scene by removing all persons from the vicinity of the incident there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool

Special protective equipment for Firefighters: Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN469 will provide a basic level of protection for chemical incidents

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding area. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel."

6.2 Environmental Precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air)

6.3 Methods and material for containment and cleaning up

Small spill: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.

6.4 Reference to other sections : See Section 1 for emergency contact information
See Section 8 for information appropriate personal protective equipment
See Section 13 for additional waste treatment information

7. HANDLING AND STORAGE

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s)

7.1 Precautions for safe handling

Protective measures: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container. Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

Advice on general occupational hygiene: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities: Storage temperature 5 to 25°C (41 to 77°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

Recommendations: Not available

Industrial sector specific solutions: Not available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s)

8.1 Control parameters

Occupational exposure limits

Product / ingredient name	Exposure limit values
2-ethylhexanoic acid, zirconium salt	EH40/2005 WELs (United Kingdom (UK). 12/2011). STEL: 10 mg/m ³ , (as Zr) 15 minutes TWA: 5 mg/m ³ , (as Zr) 8 hours

Recommended monitoring procedures: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
Hydrocarbons, C9-C11 n-alkalines, isoalkanes cyclics, <2% aromatics	DNEL	Long term Dermal	208 mg/kg bw/day	Workers	Systemic
	DNEL	Long term inhalation	871 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	125 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term inhalation	185 mg/m ³	Consumers	Systemic
	DNEL	Long term Oral	125 mg/kg bw/day	Consumers	Systemic
2-butanone oxime	DNEL	Long term Inhalation	9 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	3.33 mg/m ³	Workers	Local
	DNEL	Long term Dermal	1.3 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	2.5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	2.7 mg/m ³	Consumers	Systemic
	DNEL	Long term Inhalation	2 mg/m ³	Consumers	Local
	DNEL	Long term Dermal	0.78 mg/kg bw/day	Consumers	Systemic
DNEL	Short term Dermal	1.5 mg/kg bw/day	Consumers	Systemic	

PNECs

Product/ingredient name	Type	Compartment Detail	Value	Method Detail
2-butanone oxime	-	Fresh water	0.256 mg/l	Assessment Factors
	-	Sewage treatment plant	177mg/l	Assessment Factors

8.2 Exposure controls

Appropriate engineering controls: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection: Safety glasses with side shields.

Skin protection

Hand Protection: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Gloves: For prolonged or repeated handling, use the following type of gloves: Recommended: nitrile rubber

Body protection: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Other skin protection: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and risks involved and should be approved by a specialist before handling this product.

Respiratory protection: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Environmental exposure controls: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance

Physical state	: Liquid
Colour	: Various
Odour	: Hydrocarbon [slight]

Odour threshold	: Not available
pH	: Insoluble in water
Melting/freezing point	: May start to solidify at the following temperature: -15°C (5°F). This is based on data for the following ingredient: Hydrocarbons C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics. Weighted average: -60.61°C (-77.1°F)
Initial boiling point & boiling range	: 145°C
Flash point	: Closed cup: 43°C
Evaporation rate	: Highest known value: 0.04 (Hydrocarbons C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics). Weighted average: 0.03 compared with butyl acetate
Material supports combustion	: Yes
Flammability (solid, gas)	: Liquid
Upper/lower flammability or explosive limits	: Greatest known value: Lower 0.6% Upper 7% (Hydrocarbons C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Vapour pressure	: Highest known value: 0.1 to 0.3 kPa (0.8 to 2.3mm Hg) (at 20°C) (Naphtha [petroleum], hydrotreated heavy). Weighted Average: 0.16 kPa (1.2 mm Hg) (at 20°C)
Vapour density	: Highest known value: 4.5 (Air = 1) (Distillates (petroleum) hydrotreated light). Weighted average: 4.5 (Air = 1)
Relative density	: 1.43
Solubility(ies)	: Insoluble in the following materials: cold water
Partition coefficient: n-octanol/water	: Not applicable
Auto-ignition temperature	: Lowest known value: >220°C (>428°F) (Distillates (petroleum), hydrotreated light)
Decomposition temperature	: Stable under recommended storage and handling conditions (see Section 7)
Viscosity	: Kinematic (room temperature): >4cm ² /s Kinematic (40°C): >0.21cm ² /s
Viscosity	: > 100 s (ISO 6mm)
Explosive properties	: Product does not present an explosion hazard
Oxidising properties	: Product does not present an oxidising hazard

9.2 Other information

No additional information.

10. STABILITY AND REACTIVITY

10.1 Reactivity: No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability: The product is stable

10.3 Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reaction will not occur

10.4 Conditions to avoid: When exposed to high temperature may produce hazardous decomposition products. Refer to protective measures listed in Sections 7 & 8

10.5 Incompatible materials: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products: Decomposition products may include the following materials carbon oxides, metal oxide / oxides

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Naphtha (petroleum), hydrotreated heavy	LD50 Oral	Rat	>6 g/kg	-
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	LD50 Dermal	Rat	5000 mg/kg	-
	LD50 Oral	Rat	5000 mg/kg	-
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% Aromatics	LD50 Oral	Rat	>6 g/kg	-
	LD50 Oral	Rat	>6 g/kg	-
2-butanone oxime	LD50 Oral	Rat	930 mg/kg	-
2-ethylhexanoic acid, zirconium salt	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	>5 g/kg	-

Conclusion/Summary : There are no data available on the mixture itself

Acute toxicity estimates

Route	ATE value
Not available	

Irritation/Corrosion**Conclusion/Summary** : There are no data available on the mixture itself**Sensitisation****Conclusion/Summary** : There are no data available on the mixture itself**Mutagenicity****Conclusion/Summary** : There are no data available on the mixture itself**Carcinogenicity****Conclusion/Summary** : There are no data available on the mixture itself**Reproductive toxicity****Conclusion/Summary** : There are no data available on the mixture itself**Teratogenicity****Conclusion/Summary** : There are no data available on the mixture itself**Specific target organ toxicity (single exposure)**

Product/ingredient name	Category	Route of exposure	Target
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	Category 3	Not applicable	Narcotic effects

Specific target organ toxicity (repeated exposure)

Not available

Aspiration hazard

Product / ingredients name	Result
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	ASPIRATION HAZARD – Category 1
Naphtha (petroleum), Hydrotreated heavy: Nota(s) P	ASPIRATION HAZARD – Category 1
Distillates (petroleum), Hydrotreated light	ASPIRATION HAZARD – Category 1
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	ASPIRATION HAZARD – Category 1
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics	ASPIRATION HAZARD – Category 1

Information on the likely routes of exposure – Not available**Potential acute health effects****Inhalation** : No known significant effects or critical hazards.**Ingestion** : No known significant effects or critical hazards.**Skin contact** : Defatting to the skin. May cause skin dryness and irritation**Eye contact** : No known significant effects or critical hazards.**Symptoms related to the physical chemical and toxicological characteristics****Inhalation** : No specific data**Ingestion** : No specific data**Skin contact** : Adverse symptoms may include the following: Irritation, Dryness, Cracking**Eye contact** : No specific data**Delayed and immediate effects and also chronic effects from short and long term exposure****Short term exposure****Potential immediate effects:** Not available**Potential delayed effects:** Not available**Long term exposure****Potential immediate effects:** Not available**Potential delayed effects:** Not available**Potential chronic health effects**

Not available

Conclusion/Summary: Not available**General:** Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis**Carcinogenicity** : No known significant effects or critical hazards.**Mutagenicity** : No known significant effects or critical hazards.**Teratogenicity** : No known significant effects or critical hazards.**Developmental effects** : No known significant effects or critical hazards.**Fertility effects** : No known significant effects or critical hazards.**Other information** : Not available

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No. 1272/2008 and is classified for toxicological hazards accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated Occupational Exposure Limit may result in adverse health effects such as irritation of the mucous membrane and respiratory system and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 2-butanone oxime. May produce an allergic reaction.

12. ECOLOGICAL INFORMATION

12.1 Toxicity:

Product/ingredient name	Result	Species	Exposure
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics <2% aromatics	LC50 >100mg/l	Algae	72 hours

Conclusion/Summary : There are no data available on the mixture itself

12.2 Persistence and degradability:

Product/ingredient name	Test	Result	Dose	Inoculum
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics <2% aromatics	-	80 %- Readily – 28 days	-	-

Conclusion/Summary : There are no data available on the mixture itself

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics <2% aromatics	-	-	Readily
Distillates (petroleum), hydrotreated light	-	-	Readily
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics <2% aromatics	-	-	Readily

Conclusion/Summary : There are no data available on the mixture itself

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics <2% aromatics		10 to 2500	High
Distillates (petroleum), hydrotreated light	-	159	Low
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics <2% aromatics	-	159	Low
2-butanone oxime	0.63	5.01	Low

12.4 Mobility in soil

Soil/water partition coefficient (Koc): Not available

Mobility: Not available

12.5 Results of PBT and vPvB assessment

PBT: Not applicable **vPvB:** Not applicable

12.6 Other adverse effects : No known significant effects or critical hazards.

13. DISPOSAL CONSIDERATIONS

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s)

13.1 Waste treatment methods

Product

Methods of disposal: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste: Yes

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	Waste paint and varnish containing organic solvents or other dangerous substances

Packaging

Methods of disposal: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 04 metallic packaging

Special precautions: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

14. TRANSPORT INFORMATION

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN1263	UN1263	UN1263	UN1263
14.2 proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	III	III	III	III
14.5 environmental hazards	No	No	No	No
Marine pollutant substances	Not applicable	Not applicable	Not applicable	Not applicable

Additional information

ADR/RID : This class 3 viscous liquid is not subject to regulation in packagings up to 450L. according to 2.2.3.1.5

Tunnel code : (D/E)

ADN : This class 3 viscous liquid is not subject to regulation in packagings up to 450L. according to 2.2.3.1.5

IMDG : This class 3 viscous liquid is not subject to regulation in packagings up to 450L. according to 2.2.3.1.5

IATA : None identified

Special precautions for user: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Not applicable

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed

Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

VOC for Read-for-Use Mixture : IIA/e. Interior/exterior trim varnishes and woodstains, including opaque woodstains. EU Limit values: 400g/l (2010)
This product contains a maximum of 400g/l VOC

Seveso Directive

This product is controlled under the Seveso Directive

Danger criteria

Category
P5c

15.2 Chemical Safety Assessment

: No Chemical Safety Assessment has been carried out.

16. OTHER INFORMATION

Abbreviations and acronyms :

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3 H226	On basis of test data

Full text of abbreviated H.

Statements

H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H361 fd (oral)	Suspected of damaging fertility if swallowed. Suspected of damaging the unborn child if swallowed

Full text of classifications

[CLP/GHS]

Acute Tox. 4, H312	ACUTE TOXICITY (dermal) – Category 4
Asp. Tox. 1, H304	ASPIRATION HAZARD – Category 1
Carc. 2 H351	CARCINOGENICITY – Category 2
EUH066	Repeated exposure may cause skin dryness and cracking
Eye Dam. 1 H318	SERIOUS EYE DAMAGE/EYE IRRITATION – Category 1
Flam. Liq. 3, H226	FLAMMABLE LIQUIDS – Category 3
Repr. 2, H361fd (oral)	TOXIC TO REPRODUCTION (Fertility and Unborn child) (Oral) – Category 2
Skin Sens. 1, H317	SKIN SENSITIZATION – Category 1
STOT SE 3, H336	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic Effects) – Category 3

History

Date of Issue/date of revision April 2018

Date of previous issue March 2017

Prepared by – Intumescent Systems Ltd

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

HEALTH & SAFETY INFORMATION SHEET
APPENDIX 71b
HW EXCEL WHITE - GLOSS

1. IDENTIFICATION OF THE PREPARATION AND COMPANY

1.1 Product identifier

Product name : HW Excel white – Gloss
Product code : Not available
Other means of identification : Not available

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Consumer applications, Professional applications
Use of the substance/mixture : Coating

1.3 Details of the supplier of the safety data sheet

Envirograf, Envirograf House, Barrestone, Dover, Kent, CT15 7JG
Telephone/fax/email: 01304 842555 01304 842666 sales@envirograf.com

1.4 Emergency telephone number: **Supplier:** 01304 842555 (Not 24 Hours)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification According to Regulation (EC) No. 1272/2008 [CLP/GHS]: Flam. Liq. 3, H226

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended

See Section 16 for the full text of the H statements declared above

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label Elements

Hazard pictograms :



Signal word : Warning

Hazard statements : Flammable liquid and vapour

Precautionary statements

General: Keep out of reach of children. If medical advice is needed, have product container or label at hand

Prevention: Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames & other ignition sources. No Smoking

Response: IF ON SKIN (or hair): Immediately take off all contaminated clothing. Rinse skin with water or shower

Storage: Store in a well-ventilated place. Keep cool

Disposal: Dispose of contents & container in accordance with all local, regional, national & international regulations.

P102, P101, P280, P210, P303+P361+P353, P403, P235, P501

Hazardous ingredients: Not applicable

Supplemental label elements: Contains 2-butanone oxime. May produce an allergic reaction.

Annex XVII- Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles: Not Applicable

Special packaging requirements

Containers to be fitted with child-resistant fastenings: Not Applicable

Tactile warning of danger : Not applicable

2.3 Other hazards

Other hazards which do not result in classification : Prolonged or repeated contact may dry skin & cause irritation

3. COMPOSITION / INFORMATION ON INGREDIENTS

3.2 Mixtures :Mixture

Product/ingredient name	Identifiers	%	Classification Regulation (EC) No. 1272/2008 [CLP]	Type
Hydrocarbons, C9-C11 n-alkalines, isoalkanes cyclics, <2% aromatics	REACH # 01-2119463258-33 EC: 919-857-5 CAS: 64742-48-9	≥ 10- <20	Flam.Liq 3, H226 STOT SE 3, H336 Asp. Tox. 1, H226 EUH066	[1]
Naphtha (petroleum) hydrotreated heavy: Nota(s) P	EC: 265-150-3 CAS:64742-48-9 Index: 649-327-00-6	≥ 5.0 – <10	Flam. Liq. 3, H226 Asp. Tox. 1, H304 EUH066	[1]
Hydrocarbons, C10-C13, n-alkanes, Isoalkanes, cyclics <2% aromatics	REACH #: 01-2119457273-39 EC: 918-481-9 CAS: 64742-48-9	≥1 - ≥5.0	Asp. Tox. 1, H304 EUH066	[1]
Hydrocarbons, C14-C18, n-alkanes, Isoalkanes, cyclics <2% aromatics	REACH #: 01-2119457736-27 EC: 927-63-8 CAS: 64742-47-8	≥1 - ≥5.0	Asp. Tox. 1, H304 EUH066	
2-butanone oxime	REACH #: 01-2119539477-2 EC: 202-496-6 CAS: 96-29-7 Index: 616-014-00-0	<1.0	Acute Tox. 4, H312 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351 For full text of H statements declared above see section 16	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8

SUB codes represent substances without registered CAS Numbers.

4. FIRST AID MEASURES

4.1 Description of first aid

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

Inhalation: Remove to fresh air, keep patient warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin Contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or a recognized skin cleaner. DO NOT USE SOLVENT OR THINNERS.

Ingestion: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. DO NOT induce vomiting

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact : No known significant effects or critical hazards

Inhalation : No known significant effects or critical hazards

Skin contact : Defatting to the skin. May cause skin dryness and irritation

Ingestion : No known significant effects or critical hazards

Over-exposure signs/symptoms

Eye contact : No specific data

Inhalation : No specific data

Skin contact : Adverse symptoms may include: irritation, dryness, cracking

Ingestion : No specific data

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled

Specific treatments: No specific treatment.

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Use dry chemical, CO₂, water spray (fog) or foam

Unsuitable extinguishing media: Do not use water jet

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture: Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard

Hazardous combustion products: Decomposition products may include the following materials: carbon dioxide, carbon monoxide, metal oxide/oxides

5.3 Advice for firefighters

Special precautions for Firefighters : Promptly isolate the scene by removing all persons from the vicinity of the incident there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool

Special protective equipment for firefighters : Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN469 will provide a basic level of protection for chemical incidents

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding area. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flames, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel."

6.2 Environmental Precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air)

6.3 Methods and material for containment and cleaning up

Small spill: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

6.4 Reference to other Sections : See Section 1 for emergency contact information

See Section 8 for information appropriate personal protective equipment

See Section 13 for additional waste treatment information

7. HANDLING AND STORAGE

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s)

7.1 Precautions for safe handling

Protective measures: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container. Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting, self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

Advice on general occupational hygiene: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities: Storage temperature 5 to 25°C (41 to 77°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

Recommendations: Not available

Industrial sector specific solutions: Not available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s)

8.1 Control parameters

Occupational exposure limits

No exposure limit value known

Recommended monitoring procedures: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
Hydrocarbons, C9-C11 n-alkalines, isoalkanes cyclics, <2% aromatics	DNEL	Long term Dermal	208 mg/kg bw/day	Workers	Systemic
	DNEL	Long term inhalation	871 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	125 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term inhalation	185 mg/m ³	Consumers	Systemic
	DNEL	Long term Oral	125 mg/kg bw/day	Consumers	Systemic
2-butanone oxime	DNEL	Long term Inhalation	9 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	3.33 mg/m ³	Workers	Local
	DNEL	Long term Dermal	1.3 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	2.5 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	2.7 mg/m ³	Consumers	Systemic
	DNEL	Long term Inhalation	2 mg/m ³	Consumers	Local
	DNEL	Long term Dermal	0.78 mg/kg bw/day	Consumers	Systemic
	DNEL	Short term Dermal	1.5 mg/kg bw/day	Consumers	Systemic

PNECs

Product/ingredient name	Type	Compartment Detail	Value	Method Detail
2-butanone oxime	-	Fresh water	0.256 mg/l	Assessment Factors
	-	Sewage treatment plant	177mg/l	Assessment Factors

8.2 Exposure controls

Appropriate engineering controls: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection: Chemical splash goggles.

Skin protection

Hand Protection: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended.

Gloves: For prolonged or repeated handling, use the following type of gloves: Recommended: nitrile rubber

Body protection: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Other skin protection: Appropriate footwear & any additional skin protection measures should be selected based on the task being performed & risks involved & should be approved by a specialist before handling this product.

Respiratory protection: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Filter type: organic vapour (Type A) and particulate filter P3

Environmental exposure controls: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance

Physical state	: Liquid
Colour	: Various
Odour	: Hydrocarbon [slight]
Odour threshold	: Not available
pH	: Insoluble in water
Melting/freezing point	: May start to solidify at the following temperature: -15°C (5°F) This is based on data for the following ingredient: Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics. Weighted Average: -58.56°C (-73.4°F)
Initial boiling point & boiling range	: 145°C
Flash point	: Closed cup: 41°C
Evaporation rate	: Highest known value: 0.04 (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics) Weighted Average: 0.03 compared with butyl acetate
Material supports combustion	: Yes

Flammability (solid, gas)	: Liquid
Upper/lower flammability or explosive limits	: Greatest known range: Lower 0.6% Upper: 7% (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics)
Vapour pressure	: Highest known value: 0.1 to 0.3 kPa (2.3mm Hg) (at 20°C) (Naphtha (petroleum), hydrotreated heavy) Weighted Average: 0.16 kPa (1.2 mm Hg) (at 20°C)
Vapour density	: Highest known value: 4.5 (Air = 1) (Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics.)
Relative density	: 1.17
Solubility(ies)	: Insoluble in the following materials: cold water
Partition coefficient: n-octanol/water	: Not applicable
Auto-ignition temperature	: Lowest known value: >230°C (>446°F) (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics.)
Decomposition temperature	: Stable under recommended storage & handling conditions (se Section 7)
Viscosity	: Kinematic (room temperature): >4cm ² /s Kinematic (40°C): >2.1cm ² /s
Viscosity	: 60 - 100 s (ISO 6mm)
Explosive properties	: The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible
Oxidising properties	: Product does not present an oxidizing hazard

9.2 Other information

No additional information.

10. STABILITY AND REACTIVITY

10.1 Reactivity: No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability: The product is stable

10.3 Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reaction will not occur

10.4 Conditions to avoid: When exposed to high temperature may produce hazardous decomposition products. Refer to protective measures listed in Sections 7 & 8

10.5 Incompatible materials: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products: Depending on conditions, decomposition products may include the following materials: carbon oxides, metal oxide/oxides

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Naphtha (petroleum), Hydrotreated heavy Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	LD50 Oral	Rat	>6 g/kg	-
	LD50 Dermal	Rat	5000 mg/m ³	-
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% Aromatics 2-butanone oxime	LD50 Oral	Rat	5000 mg/m ³	-
	LD50 Oral	Rat	>6 g/kg	-
	LD50 Oral	Rat	930 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Acute toxicity estimates

Route	ATE value
Not available	

Irritation/Corrosion

Conclusion/Summary : There are no data available on the mixture itself.

Sensitisation

Conclusion/Summary : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	Category 3	Not applicable	Narcotic effects

Specific target organ toxicity (repeated exposure)

Not available

Aspiration hazard

Product / ingredients name	Result
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	ASPIRATION HAZARD – Category 1
Naphtha (petroleum), Hydrotreated heavy	ASPIRATION HAZARD – Category 1
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	ASPIRATION HAZARD – Category 1
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics	ASPIRATION HAZARD – Category 1

Information on the likely routes of exposure – Not available

Potential acute health effects**Inhalation** : No known significant effects or critical hazards.**Ingestion** : No known significant effects or critical hazards.**Skin contact** : Defatting to the skin. May cause skin dryness and irritation**Eye contact** : No known significant effects or critical hazards.**Symptoms related to the physical chemical and toxicological characteristics****Inhalation** : No specific data**Ingestion** : No specific data**Skin contact** : Adverse symptoms may include the following:
IrritationDrynessCracking**Eye contact** : No specific data**Delayed and immediate effects and also chronic effects from short and long term exposure****Short term exposure****Potential immediate effects** : Not available**Potential delayed effects** : Not available**Long term exposure****Potential immediate effects** : Not available**Potential delayed effects** : Not available**Potential chronic health effects**

Not available

Conclusion/Summary : Not available**General** :Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis**Carcinogenicity** : No known significant effects or critical hazards.**Mutagenicity** : No known significant effects or critical hazards.**Teratogenicity** : No known significant effects or critical hazards.**Developmental effects** : No known significant effects or critical hazards.**Fertility effects** : No known significant effects or critical hazards.**Other information** : Not available

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and classified for toxicological hazards accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated Occupational Exposure Limit may result in adverse health effects such as irritation of the mucous membrane and respiratory system and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 2-butanone oxime. May produce an allergic reaction.

12. ECOLOGICAL INFORMATION

12.1 Toxicity:

Product/ingredient name	Result	Species	Exposure
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	LC50 >100mg/l Fresh water	Algae	72 hours

Conclusion/Summary : There are no data available on the mixture itself

12.2 Persistence and degradability:

Product/ingredient name	Test	Result	Dose	Inoculum
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	-	80% - Readily – 28 days	-	-

Conclusion/Summary : There are no data available on the mixture itself

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics <2% aromatics	-	-	Readily
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics <2% aromatics	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics <2% aromatics		10 to 2500	High
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics <2% aromatics	-	159	Low
2-butanone oxime	0.63	5.01	Low

12.4 Mobility in soil

Soil/water partition Coefficient (Koc): Not available

Mobility: Not available

12.5 Results of PBT and vPvB assessment

PBT : Not applicable

vPvB : Not applicable

12.6 Other adverse effects : No known significant effects or critical hazards.

13. DISPOSAL CONSIDERATIONS

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s)

13.1 Waste treatment methods

Product

Methods of disposal: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	Waste paint and varnish containing organic solvents or other dangerous substances

Packaging

Methods of disposal: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 04 metallic packaging

Special precautions: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

14. TRANSPORT INFORMATION

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN1263	UN1263	UN1263	UN1263
14.2 proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	III	III	III	III
14.5 environmental hazards	No	No	No	No
Marine pollutant substances	Not applicable	Not applicable	Not applicable	Not applicable

Additional information

ADR/RID : This class 3 material is not subject to regulation in packagings up to 450L. according to 2.2.3.1.5

Tunnel code : (D/E)

ADN : This class 3 material is not subject to regulation in packagings up to 450L. according to 2.2.3.1.5

IMDG : This class 3 material is not subject to regulation in packagings up to 30L. according to 2.2.3.1.5

IATA : None identified

14.6 Special precautions for user: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code : Not applicable

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed

Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable

Other EU regulations

VOC for Read-for-Use : IIA/d. Interior/exterior trim and cladding paints for wood and metal. EU Limit values: 300g/l (2010)
This product contains a maximum of 300g/l VOC

Seveso Directive

This product is controlled under the Seveso Directive

Danger criteria

Category
P5c

15.2 Chemical Safety Assessment

: No Chemical Safety Assessment has been carried out.

16. OTHER INFORMATION

Abbreviations and acronyms :

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3, H226	On basis of test data

Full text of abbreviated H.

Statements

H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H351	Suspected of causing cancer

Full text of classifications

[CLP/GHS]

Acute Tox. 4, H312	ACUTE TOXICITY (dermal) – Category 4
Asp. Tox. 1, H304	ASPIRATION HAZARD – Category 1
Carc. 2 H351	CARCINOGENICITY – Category 2
EUH066	Repeated exposure may cause skin dryness or cracking
Eye Dam. 1 H318	SERIOUS EYE DAMAGE/EYE IRRITATION – Category 1
Flam. Liq. 3, H226	FLAMMABLE LIQUIDS – Category 3
Skin Sens. 1, H317	SKIN SENSITIZATION – Category 1
STOT SE 3, H336	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic Effects) – Category 3

History

Date of issue/date of revision 2nd August 2018

Date of previous issue 25th April 2017

Prepared by – Intumescent Systems Ltd

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

APPLICATION DATA SHEET



ENVIROGRAF®

AP042-EXCEL WHITE-08-2018

Product Number: 42 HW Excel White Top Coat

Description:

A solvent based product to apply over HW01 – no need for an undercoat. Available in Satin or Gloss finishes. Gives a high quality durable finish for internal & external use. Suitable for use on all types of timber substrate.

Application:

All surfaces to be painted should be clean, dry and free from loose and flaking material. Stir HW Excel well before and during use. Apply using brush or roller. HW Excel white is supplied ready for use and does not need thinning.

For internal use apply 1 coat at 10 – 12m² per litre

For external use apply 2 coats at 10 – 12m² per litre per coat

(Ensure end grain is treated with each coat)

Cleaning and storage:

Remove as much product as possible from brushes before cleaning. Clean equipment immediately after use with white spirit or turpentine substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

To avoid risk of spillage, always store and transport in a secure upright position.

STORE AWAY FROM HEAT AND FLAME

Precautions:

- Keep away from sources of ignition – No Smoking
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner. Do not use solvent or thinners.
- If swallowed seek medical advice immediately and show container or label.
- Keep out of the reach of children.