



Product Number: 69

Intumescent Surface Mounted Fire & Smoke Seals

Description:

This is a surface-mounted intumescent fire or fire and smoke seal available in black, brown, red, white, and real wood veneer finishes. No routing is necessary. Supplied as a pack with intumescent paper for use around lock and hinge areas and two labels printed "Fire Door – Keep Shut".

Use:

This product is fitted to door frames in minutes. A 3½mm or greater gap down the closing stile and across the door head is all that is required. Seals fit directly over hinges with no hinge bind and no special gap is necessary on hinge side. Once fitted the face of the seal can be painted, although the brush smoke seal must NOT be painted. If the brush is painted in error it is easy to replace. The seals have a self-adhesive backing but pins are also supplied for added security of fitting.

Ordering references:

REF	TYPE	COLOUR
ES/SDS	Single door set	Brown, white, red, black
ES/SDW	Single door set	Real wood veneer – oak, sapele, ash
ES/DDS	Double door set	Brown, white, red, black
ES/DDW	Double door set	Real wood veneer – oak, sapele, ash

REF	TYPE	COLOUR
NS/SDS	Single door set	Brown, white, red, black
NS/SDW	Single door set	Real wood veneer – oak, sapele, ash
NS/DDS	Double door set	Brown, white, red, black
NS/DDW	Double door set	Real wood veneer – oak, sapele, ash

(ES sets are fire and smoke seals but NS sets are fire seals only)

State finish required and whether rebated or open stiles on double doors.

If the gap at the closing stile and across the head of the door is less than 3mm request packs containing only 1mm thick ES/30/PS seals.

Single strips can be supplied. *Please see price list for full range and ordering information*

Test Details:

	<u>Integrity</u>	<u>Insulation</u>
Trada IT-361	66 Minutes	N/A
Trada RF 95130	56 Minutes	N/A