TECHNICAL DATA SHEET



TD077-10-2018

Product Number: 77

Intumescent Glazing Strips

Description:

A 2mm thick compressible intumescent strip, coloured black, brown, grey, red, and white, with selfadhesive tape backing, supplied in 10m long rolls. Used in steel doors, wood doors, and partitioning. The strips are fitted to beads each side of the fire-rated glazing. Although the seal is 2mm thick, it will compress to ½mm and this will not affect its performance.

Ordering References:

Toot Dotaile

| REF | PROTECTION | SIZE |
|--------|------------|-----------------------|
| G 8/10 | 1/2 hour | 8mm x 2mm x 10metres |
| G10/10 | 1/2 hour | 10mm x 2mm x 10metres |
| G15/10 | 1/2 hour | 15mm x 2mm x 10metres |
| G20/10 | 1 hour | 20mm x 2mm x 10metres |
| G23/10 | 1 hour | 23mm x 2mm x 10metres |
| | | |

Please state colour required when ordering. Other widths made to order.

| Test Details: | Integrity | Insulation |
|-------------------------|------------|------------|
| Lafarge LPL 154 | 60 Minutes | N/A |
| Fulmer Yarsley J84201/8 | 59 Minutes | N/A |
| LPC TE84847 | 33 Minutes | 33 Minutes |
| Trada FR1756 | 59 Minutes | 59 Minutes |