TECHNICAL DATA SHEET



TD079-11-2017

Product Number: 79

Glazing Bead System for Fire Doors & Screens

Description:

Glazing Bead System: A complete glazing system consisting of 2100mm long wooden beads (with bolection moulding if required) treated with Envirograf® clear intumescent coating. Standard finishes include sapele and pine (others available to order). The beads can be painted or varnished and they are supplied with the correct size pins or screws for fixing.

10mm hardwood for $\frac{1}{2}$ hour glazing with correct length pins – 2100mm 15mm softwood for $\frac{1}{2}$ hour glazing with correct length pins – 2100mm 25mm hardwood for 1 hour glazing with correct length screws – 2100mm

All beads supplied in a PVC sleeve for transit. Supplied as standard without lip, or add suffix /L to the references for a bolection moulding (lip). **Request the standard version without lip for use on partitions.** Ideal for doors or screens.

Ordering References:

REF	PROTECTION	THICKNESS	LENGTH	DOOR
30/G10	½ hour	10mm	2100mm	44mm
30/G15	½ hour	15mm	2100mm	44mm
60/G25/54	1 hour	25mm	2100mm	54mm
60/G25/44	1 hour	25mm	2100mm	44mm
Add suffix /L if bolection moulding (lip) is required.				



