



Product Number: 152

### Suspended Ceiling Barrier

#### Description:

Suspended Ceiling Barrier for use over suspended ceiling tiles giving 60 minutes fire protection, acoustic protection impact & airborne, thermal insulation.

#### **Special features**

- Made to fit over all tile styles.
- Can be supplied to accommodate down lighters or air conditioning units.
- Made from a 60 minutes fire rated cloth adhered to a 40mm Class 0 & 1 sponge (as used with our under-floor fire barrier).
- Tested to BS476 Parts 20, 21, 22, 23 (1987)

- 1 hour fire resistant

Thickness 40mm, sound resistant, tested to BS EN ISO 140 Part 4 for airborne sound reduction mean result Dntw 65 dB.

- Thermal conductivity U value 0.27W/m<sup>2</sup>K
- Easy and quick to apply, no special clothing or gloves required. Non fibrous, can be used in sterile areas, Hospitals, computer rooms, etc.

<p><b>CB1</b> 600 x 600 weight 0.6kg <b>CB2</b> 600 x 1200 weight 1.2 kg</p>
--

If down lighters are installed, this product can be ordered in conjunction with Product 32 Acoustic Down lighter Cover (It's vital to state the position of the down lighters, as we will accommodate this product onto the barrier during the manufacturing process for ease of installation).

If air conditioning units are installed, this product can be used in conjunction with Product 31 Air Conditioning Units Covers (please also state their position).