

# APPLICATION DATA SHEET



**ENVIROGRAF®**

AP055-RS/FFCB-10-2018

## Product Number: 55 Rainscreen Fast Fix Cavity Barrier

### **Description:**

An effective solution for ventilated rainscreen cavities available in a range of sizes allowing for a continuous air gap of up to 25mm and up to 40mm. The Fast Fix cavity barrier combines high-density rock fibre with intumescent coating on both sides and an intumescent strip which, in the event of a fire will seal the ventilation gap. Supplied in 1220mm lengths with 3 fixing brackets per length.




Rainscreen Fast Fix Cavity Barrier



3 brackets supplied for every 1220mm barrier

### **Application:**

Suitable for both horizontal and vertical applications. The fixing brackets supplied need to be mechanically fixed to the substrate using non-combustible fixings. Fit the brackets at 500mm centres then push the lengths of barrier onto the brackets ensuring they are centred in the middle of the barrier and that the barrier is pushed fully back against the substrate. When fitting the barriers ensure that the brown-faced intumescent strip is facing forward. Note: the intumescent strip is colour-coded with white pins for a 25mm airflow gap and red pins for a 40mm airflow gap.



Brackets are easily pushed into the barrier



Suitable for both horizontal and vertical fitting