



### Product Number: 55 Rainscreen Fast Fix Cavity Barrier

#### Description:

An effective solution for ventilated rainscreen cavities available in a range of sizes allowing for a continuous air gap of up to 25mm and up to 40mm. The Fast Fix cavity barrier combines high-density rock fibre with intumescent coating on both sides and an intumescent strip which, in the event of a fire will seal the ventilation gap. Supplied in 1200mm lengths with 4 fixing brackets per length.

#### Ordering References:

*Supplied in 1200mm lengths.*

#### 25mm Airflow Gap (white pins)

REF	CAVITY WIDTH	WIDTH	THICKNESS	AIRFLOW GAP
RS/FFCB/50/25	75mm	50mm	60mm	25mm
RS/FFCB/60/25	85mm	60mm	60mm	25mm
RS/FFCB/75/25	100mm	75mm	60mm	25mm
RS/FFCB/100/25	125mm	100mm	60mm	25mm
RS/FFCB/150/25	175mm	150mm	60mm	25mm
RS/FFCB/175/25	200mm	175mm	60mm	25mm
RS/FFCB/200/25	225mm	200mm	60mm	25mm
RS/FFCB/225/25	250mm	225mm	60mm	25mm
RS/FFCB/250/25	275mm	250mm	60mm	25mm
RS/FFCB/275/25	300mm	275mm	60mm	25mm

#### 40mm Airflow Gap (red pins)

REF	CAVITY WIDTH	WIDTH	THICKNESS	AIRFLOW GAP
RS/FFCB/50/40	90mm	50mm	60mm	40mm
RS/FFCB/60/40	100mm	60mm	60mm	40mm
RS/FFCB/75/40	115mm	75mm	60mm	40mm
RS/FFCB/100/40	140mm	100mm	60mm	40mm
RS/FFCB/150/40	190mm	150mm	60mm	40mm
RS/FFCB/175/40	215mm	175mm	60mm	40mm
RS/FFCB/200/40	240mm	200mm	60mm	40mm
RS/FFCB/225/40	265mm	225mm	60mm	40mm
RS/FFCB/250/40	290mm	250mm	60mm	40mm
RS/FFCB/275/40	315mm	275mm	60mm	40mm

#### Test Details:

Chiltern International Fire IF11057 to BS EN 1363-1: 1999