

APPLICATION DATA SHEET



ENVIROGRAF®

AP158-MBFR-04-2023

Product Number: 158

MOULDBLOK FR

Description:

MOULDBLOCK FR, Mould-resistant fire-resistant coat is a fire protection coating which can be applied onto internal walls and ceilings, including lath and plaster surfaces. Tested to BS476 Part 20 (1987) to give up to one hour of fire protection.

Preparation & Application:

Clean all walls or ceilings, taking off any loose paint and removing all wall or ceiling paper. Any grooves or cracks in the ceiling or walls can be made good with Envirograf® Intumescent Cement – Product 63 or AM Intumescent Mastic – Product 58.

Should it be found that MOULDBLOK FR will not adhere to the existing coating, then either apply a PVA Adhesive Coating at a 50/50 ratio of adhesive to water, or apply 1 coat of Envirograf® MOULDBLOK AP Primer at 14 m² per litre. Then apply 2 coats of MOULDBLOK FR at the rate of 8 m² per litre, per coat. The approximate drying time is 1 hour. This coating is applied by brush or roller and must be applied using rubber gloves. Care must be taken to keep it off the skin and away from eyes during application.

Should you wish to overcoat MOULDBLOCK FR please use MOULDBLOCK EX.

Tools:

Leave brush in cold soapy water then clean with brush cleaner.